

New construction housing with IC housing option available Trim fixture designed to conceal internal hardware Trimless fixture features a proprietary aluminum mudding flange Machined aluminum double gimbals. Adjustable and lockable Regressed LED source for enhanced glare control Lumen range of 1000lm to 3000lm 2 SDCM, Citizen LED source available in 30K and 35K (80+ CRI)



10 DAY QUICKSHIP

Universal voltage, 0-10V integral driver with 100-1% dimming range Max Order Size: 50 pcs **ORDERING INFORMATION** PROJECT: TYPE: CATALOG #: DATE: **LUMEN OUTPUT** CAT. NO **BEAM ANGLE** VOLTAGE CRI **COLOR TEMP** 3GQ-RC1 **10 -** 1000 LUMENS **\$80 -** 80+ CRI **30K -** 3000K 20D - 20° **UNV - 120/277V 15 -** 1500 LUMENS **35K -** 3500K **40D -** 40° **22 -** 2200 LUMENS **60D -** 60° **30 -** 3000 LUMENS DRIVER **FLANGE TYPE GIMBAL FINISH HOUSING INTERIOR DIM -** 0-10V (STANDARD 100-1%) NG - NATURAL ALUMINUM WT - WHITE TRIM (STANDARD) **BK -** BLACK XTR - TRIMLESS **BG** - BLACK WG - WHITE **HOUSING TYPE OPTIONS** NC - NEW CONSTRUCTION (NON-IC) CP - CHICAGO PLENUM IC - IC HOUSING 1 - BAR HANGERS вн **SF70** - SOFTENING LENS **HXB70 -** BLACK HEXCELL LOUVER Maximum 3 optical accessories

1 IC Housing available up to 2200lm





1 LIGHT MADISON - TRIM & TRIMLESS

TRIM HOUSING OPTIONS

NC - New Construction (Non-IC)

IC - IC Housing (2200lm max)
CP - Chicago Plenum Housing

| LUMEN OUTPUT | Α | В |
|--------------|-----|-----|
| Up to 2200lm | 45° | 45° |
| 3000lm | 35° | 35° |

LUMEN OUTPUT

Up to 2200lm


3000lm


В


45°


35°

45°









TRIMLESS HOUSING OPTIONS

NC - New Construction (Non-IC)

IC - IC Housing (2200lm max)

CP - Chicago Plenum Housing

| 11.49" | - |
|--------|---|
| В | |

| | - |
|-------|---|
| 5.75" | |
| 7.69" | |

