




3G-SKU401
 4" SQUARE KUBO
 SURFACE MOUNTED



Featuring a white sandblasted acrylic diffuser with mitered corners
 Proprietary LED source fully saturates the hand fabricated acrylic
 Evenly illuminated sides with distinctive lines
 Standard and high lumen output options
 Suitable for ceiling or wall applications
 1% dimming standard with several remote driver options

ORDERING INFORMATION

PROJECT:	<input type="text"/>	TYPE:	<input type="text"/>
CATALOG #:	<input type="text"/>	DATE:	<input type="text"/>

CAT. NO	LUMEN OUTPUT	CRI	COLOR TEMP	VOLTAGE	DRIVER
3G-SKU401	L2 - STANDARD OUTPUT	S80 - 80+ CRI	27K - 2700K	UNV - 120/277V 347 - 347V (0-10V ONLY)	RDIM - REMOTE 0-10V (100-1%)
	L4 - HIGH OUTPUT		30K - 3000K		RDO1 - REMOTE 0-10V (100-0.1%)
			35K - 3500K		RDALI - REMOTE DALI (100-0.1%)
			40K - 4000K		RDHL2 - REMOTE LUTRON HI-LUMEN LDE1 (1% ECOSYSTEM)
					RLE - REMOTE PHASE DIMMING (TRIAL/ELV, 100-1%)

FINISH	
WH - WHITE (STANDARD)	
SV - SILVER	
BK - BLACK	

1 DALI-2 (Type 6) provided as standard. Please consult factory for DALI (Type 8) options

OCTOBER 8, 2020





3G-SKU401

4" SQUARE KUBO - SURFACE MOUNTED

PERFORMANCE CHART (BASED ON 80+ CRI AND 3500K SOURCE)

LED SYSTEM	DELIVERED LUMENS	SYSTEM WATTS	EFFICACY (LPW)
L2 - STANDARD OUTPUT	460	5.1	90
L4 - HIGH OUTPUT	63	11	

PRELIMINARY

LUMEN OUTPUT ADJUSTMENT FACTORS	CCT	Multiplier
	2700K	0.94
	3000K	0.97
	3500K	1.00
	4000K	1.01



TECHNICAL**HOUSING**

White sandblasted acrylic diffuser with mitered corners
Fixture collar made from cold rolled steel with powder coated finish
24 gauge LED reflector with high reflectance white powder coated finish
Standard polyester powder coated matte white finish. Optional finishes available

ELECTRICAL

Standard 0-10V, constant current drivers with 100-1% dimming range and >0.9 power factor
Standard 120/277V universal voltage drivers. Optional 347V, 0-10V drivers
Lutron EcoSystem and eidoLED DALI options available with 100-1% dimming range
All drivers are integral and easily accessible through luminaire aperture

LED SYSTEM

Proprietary LED system with color consistency <3 SDCM
Available in 27K, 30K, 35K, and 40K
Standard 80+CRI
L90 >60,000 hours
5 Year Warranty

MOUNTING

Fixture collar mounts to a standard junction box
Suitable for various ceiling applications (see mounting details)
Suitable for various grid ceiling applications (see mounting details)


LISTING

ETL listed and tested to cUL standards. Suitable for dry or damp locations

WARRANTY

5 Year Warranty on LED and drivers
Manufacturer 1 Year Warranty for defects in material and workmanship under normal use
Ambient temperature at fixture should not exceed 25°C

DRAWINGS AND DIMENSIONS



MOUNTING

