4.5" diameter high performance cylinder
Companion to 3G-DL45R series downlight family
Extruded aluminum housing with powder coated finish
Twist and lock construction and no visible hardware
Regressed LED source for enhanced glare control
Lumen range up to 3000lm (80+, 90+, and 97+ CRI options)
1% dimming standard with several integral driver options



10 DAY QUICKSHIP

Max Order Size: 50 pcs							
ORDERING INFORMATION							
PROJECT:					TYPE:		
CATALOG #:				DATE:			
CAT. NO	FIXTURE HEIGHT		LUMEN OUTPUT	CRI	COLOR TE	MP	BEAM ANGLE
3GQ-SDL45RF	7H - 7" HEIGHT 11H - 11" HEIGHT		10 - 1000 LUMENS 15 - 1500 LUMENS 22 - 2200 LUMENS 30 - 3000 LUMENS	S80 - 80+ CRI H90 - 90+ CRI	30K - 3000K 35K - 3500K 40K - 4000K		20D - 20° 40D - 40° 60D - 60° 90D - 90° * * 90D reflector supplied standard with lens
VOLTAGE		DRIVER		HOUSING FINISH		INSERT FINISH	
UNV - 120/277V 120 - 120V		DIM - 0-10V (100-1%) LE - PHASE DIM (TRIAC/ELV, 100-1%)		WH-WHITE BK - BLACK SV - SILVER		WI - WHITE BI - BLACK SI - SILVER	
OPTIONS							
EMR - EMERGENCY BATTERY (REMOTE) Maximum 1 optical accessory							

DRAWINGS AND DIMENSIONS 11" HEIGHT

