

4.5" high performance fixed downlight
Regressed LED source for enhanced glare control
Lumen range of 1000lm to 2200lm
2 SDCM, Citizen LED source available in 30K and 35K (80+ CRI)
Universal voltage, 0-10V driver with 100-1% dimming range
Shallow housing available along with other housing options



10 DAY QUICKSHIP Max Order Size: 50 pcs

									Max Order Size: 50 pcs
ORDERING INFORMATION									
PROJECT:							TYPE:		
CATALOG #:							DATE:		
CAT.NO	LUMEN OUTPUT		CRI			COLOR TEMP	BEAM ANGLE		VOLTAGE
3GQ-DL45RF	10 - 1000 LUMENS 15 - 1500 LUMENS 22 - 2200 LUMENS				30K - 3000K 35K - 3500K	20D - 20° 40D - 40° 60D - 60°		UNV - 120/277V	
DRIVER		FLANGE TYPE		BEVELED INSERT	HOUSING TYPE			OPTIONS	
DIM - 0-10V (STANDARD 100-1%)		WT - WHITE XTR - TRIMLESS		WI - WHITE	NC-	SH - SHALLOW HOUSING (IC RATED & CP RATED NC - NEW CONSTRUCTION HOUSING (NON-IC) IC - NEW CONSTRUCTION IC HOUSING		CP - CHICAGO PLENUM BH - C-CHANNEL BAR HANGERS SF70 - SOFTENING LENS (SUPPLIED STANDARD) Maximum 1 optical accessory (not available with shallow housing)	

Refer to standard specification sheets for complete details. Please note that only options shown above qualify for 10 day 3GQ program EDITION 12/19





TRIM HOUSING OPTIONS

SH - Shallow Housing (IC and Chicago Plenum Rated) (2200lm max)


3.50"


|-4.58"-|
|-5.50"-|

14.3/16" (MIN)
26" (MAX)

|-12.80"-|
|-15.00"-|

NC - New Construction Housing (Non-IC) (Chicago Plenum Rated) **IC -** New Construction IC Housing





TRIMLESS HOUSING OPTIONS

SH - Shallow Housing (IC and Chicago Plenum Rated) (2200lm max)

3.50"

|-4.58"-|
|-7.75" |
|-12.58"||-12.80" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.00" |
|-15.0

NC - New Construction Housing (Non-IC) (Chicago Plenum Rated) **IC -** New Construction IC Housing

