

3G-PDL33RA

3" ADJUSTABLE DOWNLIGHT
CYLINDER 7" AND 11" HEIGHT
DIM TO WARM



90+ CRI Dim-to-Warm LED system (3000K–1800K)
Delivered lumen output up to 1,500 lm at 90+ CRI
Performance up to 93 LPW at 90+ CRI
Regressed LED source for enhanced glare control
20° to 90° beam angle options
0°–90° tilt and 360° rotation
Field-replaceable reflectors

OPTICS




PERFORMANCE


LUMEN OUTPUT	DELIVERED LUMENS	SYSTEM WATTS	EFFICACY (LPW)
750	750	10.2	74
1000	1000	13.4	75
1250	1250	17.5	72
1500	1500	21.3	70

BASED ON 90+ CRI, 3000K, 40D OPTIC WITH SOFTENING LENS
Lumen output and actual wattage may vary +/- 5%

DIMENSIONS

STEM SUSPENSION





SUITABLE FOR
SLOPED CEILING

3G LIGHTING

3G-PDL33RA
3" ADJUSTABLE DOWNLIGHT CYLINDER - 7" AND 11" HEIGHT - DIM TO WARM

ORDERING INFORMATION

PROJECT:		**TYPE:**			
CATALOG#:		**DATE:**		**QTY:**	

CAT. NO	FIXTURE HEIGHT	LED SOURCE	LUMEN OUTPUT	CRI	BEAM ANGLE
3G-PDL33RA	**7H -** 7" HEIGHT [1] **11H -** 11" HEIGHT [2]	**DW -** DIM TO WARM (3000K-1800K)	**07 -** 750 LUMENS **10 -** 1000 LUMENS **12 -** 1250 LUMENS **15 -** 1500 LUMENS All lumen outputs are **delivered lumens** at 90+ CRI	**H90 -** 90+ CRI	**20D -** 20° [3] **40D -** 40° **60D -** 60° **90D -** 90° [4]

VOLTAGE	DRIVER	HOUSING FINISH	INSERT FINISH	CANOPY
UNV - 120/277V **120 -** 120V	**DIM -** 0-10V (100-1%) **LE -** PHASE DIM [5] (TRIAC/ELV, 100-1%) **D01 -** 0-10V (100-0.1%) **DALI -** DALI (100-1%) [6] **DHL2 -** LUTRON HI-LUME LDE [7] (100-1%) **DMX -** DMX (100-0%) [7]	**WH -** WHITE **BK -** BLACK **SV -** SILVER	**WI -** WHITE **BI -** BLACK **SI -** SILVER	**CN -** CANOPY (STANDARD) **PC -** POWER CANOPY **CF -** CONDUIT FEED CANOPY

CANOPY FINISH	SUSPENSION TYPE	SUSPENSION LENGTH	OPTIONS
WCF - WHITE (STANDARD) **BCF -** BLACK **SCF -** SILVER	**RSW -** WHITE RIGID STEM **RSB -** BLACK RIGID STEM **RSS -** SILVER RIGID STEM	**S48 -** 48" STEM **S96 -** 96" STEM All suspension options are field cuttable	**SF -** SOFTENING LENS [8] (SUPPLIED STANDARD) **LS -** LINEAR SPREAD LENS **SB -** SANDBLASTED LENS **EMR -** EMERGENCY BATTERY [9] (REMOTE) Maximum 1 optical accessory

1 7H available up to 750lm with integral driver. Select "PC" Power Canopy for 750lm, 1000lm, 1250lm options. Not available with 1500lm option
2 11H available up to 1250lm with integral driver. Select "PC" Power Canopy for 1500lm option
3 20D reflector available up to 1000lm
4 90D lens optic not available with other lens options
5 Phase dimming options available in 120V only
6 DALI-2 (Type 6) provided as standard
7 DHL2 (Lutron) and DMX not available with 7H model or "PC" Power Canopy option
8 Softening lens not provided with 90D optic
9 Supplied with enclosure that contains both Emergency Battery and driver. Installed remotely by others. Not accessible through fixture aperture

PERFORMANCE

LUMEN OUTPUT	DELIVERED LUMENS	SYSTEM WATTS	EFFICACY (LPW)
750	750	10.2	74
1000	1000	13.4	75
1250	1250	17.5	72
1500	1500	21.3	70

BASED ON 90+ CRI, 3000K, 40D OPTIC WITH SOFTENING LENS
Lumen output and actual wattage may vary +/- 5%

MULTIPLIERS

BEAM ANGLE	
20D	1.24
40D	1.00
60D	0.96
90D	0.90

HOUSING

Extruded aluminum housing with powder coated finish
Adjustable swivel mechanism with 0-90° tilt and 360° rotation

BEVELED INSERT

Cast aluminum beveled insert with matte powder coated finish
3" aperture with regressed LED source for enhanced glare control

OPTICS

Proprietary anodized, aluminum reflectors
Beam angle available in 20°, 40°, 60° and 90°
Reflectors are field replaceable (20° reflector not interchangeable)
Softening lens supplied standard

LED SYSTEM

Standard 90+ CRI
Dim to Warm (3000K-1800K)
Color consistency <3 SDCM
L90 > 42,000 hours

ELECTRICAL

Standard 0-10V, constant current drivers
100-1% dimming range and >0.9 power factor
Standard 120/277V universal voltage with several driver options
120V Forward Phase/Reverse Phase driver option (100-1%)
Integral drivers are easily accessible through luminaire aperture
Remote drivers supplied with enclosure

EMERGENCY

7W output for 90 minutes (+/- 525lm at 90+ CRI). Title 24 Certified
Remote emergency battery (not accessible through fixture aperture)
Maximum remote mounting distance: 50ft (12AWG) or 25ft (14AWG)
Caution: Emergency Battery utilizes more than one power source and servicing should be performed by qualified personnel

MOUNTING

1/2" diameter rigid stem option with sloped ceiling adapter (field cuttable)
All hardware included for mounting to 4" octagonal junction box
Canopy provided in white finish as standard
Power Canopy provided with integral driver (white finish standard)
Conduit feed cut-out canopy option designed to mount to 4" octagonal junction box


LISTING

ETL listed and conforms to UL1598 standard
Certified to CSA22.2 NO.250.0.
Declare® LBC Red List Free
Rated for dry or damp locations


WARRANTY

5 year limited warranty
LED system rated for operation in ambient environments up to 25°C


CN - STANDARD CANOPY
RECESSED J-BOX (BY OTHERS)




CN - STANDARD CANOPY
SURFACE MOUNT J-BOX (BY OTHERS)




PC - POWER CANOPY
RECESSED J-BOX (BY OTHERS)




PC - POWER CANOPY
SURFACE MOUNT J-BOX (BY OTHERS)




CF - CONDUIT FEED CANOPY
SURFACE MOUNT J-BOX (BY OTHERS)




CF - CONDUIT FEED CANOPY &
PC - POWER CANOPY
SURFACE MOUNT J-BOX (BY OTHERS)





CONDUIT COVER
3 PROVIDED WITH EACH
CONDUIT FEED CANOPY



BLANK
2 PROVIDED WITH EACH
CONDUIT FEED CANOPY

Declare® is a product transparency program administered by the International Living Future Institute (ILFI), providing standardized disclosure of product ingredients, manufacturing location, service life, end-of-life pathways, and Living Building Challenge compliance status.

PRODUCT FAMILY COVERAGE — CYLINDERS

Cylinder luminaires for surface, pendant, and wall-mounted applications. Available with multiple beam angles, lumen packages, and 95+ CRI as standard. Options include low-glare optical control, UGR-rated configurations, multiple mounting and canopy systems, adjustable downlight modules, dual-axis gimbals, and low-glare multicell optics.

LBC RED LIST FREE

This product family carries a Declare® designation of LBC Red List Free, the highest designation within the Declare program. Products with this designation contain no intentionally added Red List chemicals above applicable Declare reporting thresholds and have been evaluated against the Living Building Challenge Red List.

Red List Free
INTERNATIONAL LIVING FUTURE INSTITUTE™

BUILDING CERTIFICATION PROGRAMS

Material transparency documentation is increasingly requested as part of building certification programs and owner standards. Declare labels may be used as supporting documentation for project teams pursuing:

- Living Building Challenge (LBC)
- WELL Building Standard™ v1
- WELL Building Standard™ v2
- LEED®
- Other material disclosure and material health initiatives

Project certification requirements are determined at the building level and should be evaluated by the project team.

Declare℠

Cylinders
3G Lighting

Final Assembly: Woodbridge, Ontario, Canada
Life Expectancy: 7+ Year(s)
End of Life Options: Recyclable (95%), Landfill (5%)

Ingredients:

Aluminum UNS A96063; Steel, cold roll UNS G10080; Copper UNS C11000; Pulp, cellulose; Aluminum diethylphosphinate; Benzene, ethenyl-, polymer with 1,3-butadiene, hydrogenated; Distillates (petroleum), hydrotreated heavy naphthenic; Polypropylene; Paper; Tin, Organic; Starch, base-hydrolyzed, borated; 2,4,8,10-Tetraoxa-3,9-diphosphaspiro[5.5]undecane, 3,9-bis[2,4-bis(1,1-dimethylethyl)phenoxy]-; Vinyl acetate; Phosphorus; Iron; Zinc; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-

Living Building Challenge Criteria: Compliant

I-13 Red List:
■ LBC Red List Free
□ LBC Red List Approved
□ Declared

% Disclosed: 100% at 100ppm
VOC Content: Not Applicable

I-10 Interior Performance: Not Applicable
I-14 Responsible Sourcing: Not Applicable

GLG-0002
EXP. 01 JUN 2027
Original Issue Date: 2026

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY
INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare