

3G LIGHTING


3GR-58RMSL

5.8" CURVED RECESSED SLOT
MADISON


Solid aluminum double gimbal with dual axis adjustability
Individual fixture heads can be repositioned in either direction (up to 18")
Standard 95+ CRI LED system with performance up to 126 LPW
Delivered lumen range up to 4366lm at 95+ CRI
Regressed LED source for enhanced glare control
10° to 90° beam angle options suitable for various applications
Companion to 3G's Madison product family




WT - TRIM




XTR - TRIMLESS



FX - FLANGELESS



OPTICS









PERFORMANCE

LUMEN OUTPUT	DELIVERED LUMENS	SYSTEM WATTS	EFFICACY (LPW)
1000	1000	8.7	115
1500	1500	13.1	115
2000	2000	18.6	108
2500	2500	23.2	108
3000	3000	29.5	102
3500	3500	34.7	101
4000	4000	39.5	101

BASED ON 95+ CRI, 35K, 40D OPTIC
Lumen output and actual wattage may vary +/- 5%

SHAPES

This product is designed to be specified using our online configurator. The following configurations are standard offerings.
For customized layouts, see page 7 for instructions

RING	CAPSULE	L-SHAPE
		
More details on page 5	More details on page 5	More details on page 6
U-SHAPE	SQUARE	RECTANGLE
		
More details on page 6	More details on page 6	More details on page 6

USE ONLINE CONFIGURATOR TO SPECIFY THIS PRODUCT LINE. [CONFIGURE](#)

PROJECT:		TYPE:	
CATALOG#:		DATE:	QTY:

CAT. NO	LUMEN OUTPUT	CRI	COLOR TEMP	BEAM ANGLE	VOLTAGE
3GR-58RMSL	10 - 1000 LUMENS 15 - 1500 LUMENS 20 - 2000 LUMENS 25 - 2500 LUMENS 30 - 3000 LUMENS 35 - 3500 LUMENS 40 - 4000 LUMENS All lumen outputs are delivered lumens at 95+ CRI	H95 - 95+ CRI	27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K	10D - 10° ¹ 20D - 20° 40D - 40° 60D - 60° 90D - 90° * *90D optic supplied with lens Not available with other lens options	UNV - 120/277V 120 - 120V 347 - 347V ²

DRIVER	TRIM FLANGE	GIMBAL FINISH	HOUSING FINISH
DIM - 0-10V (100-1%) LE - PHASE DIM ³ (TRIAC/ELV, 100-1%) D01 - 0-10V (100-0.1%) DALI - DALI (100-1%) ⁴ DHL2 - LUTRON HI-LUME (1% ECOSYSTEM) DMX - DMX (100-0%)	WT - WHITE TRIM (STANDARD) BT - BLACK TRIM XTR - TRIMLESS (MUD-IN DRYWALL) FX - FLANGELESS	NG - NATURAL ALUMINUM BG - BLACK GIMBAL WG - WHITE GIMBAL	BK - BLACK (STANDARD) WH - WHITE

OPTIONS	RUN TYPE	RADIUS	RADIUS DOWNLIGHTS	TOTAL DOWNLIGHTS
CP - CHICAGO PLENUM EMR - EMERGENCY BATTERY ⁵ (REMOTE) 2C - 2 CIRCUIT OPERATION 3C - 3 CIRCUIT OPERATION SF - SOFTENING LENS LS - LINEAR SPREAD LENS SB - SANDBLASTED LENS HXB - BLACK HEXCELL LOUVER *Lens options not available with 90D optic Maximum 2 optical accessories	O - ____' (RING) P - ____'x ____' (CAPSULE) L - ____'x ____' (L-SHAPE) U - ____'x ____'x ____' (U-SHAPE) SQ - ____'x ____' (SQUARE) R - ____'x ____' (RECTANGLE) CUS - CUSTOM SHAPE (PLEASE SUBMIT DRAWING TO 3G) *Product is designed to be specified using our online configurator. CONFIGURE	RA - ____' *Ring and Capsule shapes do not require Radius selection	RL - ____'	DL - ____'

¹ 10D and 20D reflector available up to 2000lm
² 347 available in "DIM" 0-10V only (100-1%)
³ Phase dimming options available in 120V only
⁴ DALI-2 (Type 6) provided as standard
⁵ Supplied with enclosure with Emergency Battery and driver. Installed remotely by others. Not accessible through fixture aperture

PERFORMANCE

LUMEN OUTPUT	DELIVERED LUMENS	SYSTEM WATTS	EFFICACY (LPW)
1000	1000	8.7	115
1500	1500	13.1	115
2000	2000	18.6	108
2500	2500	23.2	108
3000	3000	29.5	102
3500	3500	34.7	101
4000	4000	39.5	101

BASED ON 95+ CRI, 35K, 40D OPTIC
Lumen output and actual wattage may vary +/- 5%

HOUSING

Housing constructed in extruded aluminum and cold rolled steel
Designed for continuous runs in various configurations
Maximum ceiling thickness of 1.75". Consult factory for modifications
Standard matte black powder coated housing finish
Trim flange with power coated finish and 0.400" overlap
Trimless model features a perforated galvanized mudding flange

ADJUSTABILITY

Solid aluminum double gimbal with dual axis adjustability
Individual fixture heads can be repositioned within channel
Movement allowable up to 18" in either direction
Each double gimbal can be locked in place

OPTICS

Proprietary anodized, aluminum reflectors
Beam angle available in 10°, 20°, 40° and 60°, and 90°
Reflectors are field replaceable
10° and 20° reflectors are multi-faceted (not interchangeable with other options)

LED SYSTEM

Standard 95+ CRI
Color consistency <2 SDCM
Available in 27K, 30K, 35K, and 40K
L90 > 50,000 hours

ELECTRICAL

Standard 0-10V, constant current drivers
100-1% dimming range and >0.9 power factor
Standard 120/277V universal voltage with several driver options
120V Forward Phase/Reverse Phase driver option (100-1%)
Integral drivers are easily accessible through luminaire aperture

MULTIPLIERS

BEAM ANGLE	
10D	0.92
20D	1.07
40D	1.00
60D	1.00
90D	0.90

COLOR TEMP	
2700K	0.98
3000K	1.00
3500K	1.00
4000K	1.02

EMERGENCY

7W output for 90 minutes (One fixture head +/- 850lm at 95+ CRI)
Title 24 Certified
Remote emergency battery not accessible through fixture aperture
Maximum remote mounting distance:
3000lm or below - 50ft (12AWG) or 25ft (14AWG)
Above 3000lm - 30ft (12AWG) or 20ft (14AWG)
Caution: Emergency Battery utilizes more than one power source and servicing should be performed by qualified personnel

MOUNTING

New construction housing suspended via 1/4" threaded rod or suspension cables (by others)
Trim fixture designed for use in drywall, wood, and other architectural ceiling materials
Trimless fixture designed for use in drywall, mud-in ceiling applications
Flangeless fixture designed for use in wood ceilings

LISTING


ETL listed and conforms to UL1598 standard
Certified to CSA22.2 No.250.0.
Rated for dry or damp locations

WARRANTY

5 year limited warranty
LED system rated for operation in ambient environments up to 25°C


HARD CEILING

WT - TRIM




RECOMMENDED CEILING
CUT-OUT 6.25"

XTR - TRIMLESS




RECOMMENDED CEILING
CUT-OUT 6.25"

FX - FLANGELESS




RECOMMENDED CEILING
CUT-OUT 5.90"




TRIM



TRIMLESS (MUD-IN DRYWALL)




FLANGELESS




GIMBAL ADJUSTABILITY

WIDTH



LENGTH




LUMEN OUTPUT	A	B	C
Up to 3000lm	45°	45°	30°
4000lm	45°	45°	20°

USE ONLINE CONFIGURATOR TO SPECIFY THIS PRODUCT LINE. [CONFIGURE](#)

RING

RUN TYPE	TOTAL DOWNLIGHTS
☒ - RING ☐ - RING	12
10' DIAMETER	



Step 1: Select diameter: **2'-60'**


Step 2: Select the total number of downlights

Configurator Logic: Downlight options scale with diameter selection

USE ONLINE CONFIGURATOR TO SPECIFY THIS PRODUCT LINE. [CONFIGURE](#)

CAPSULE (PILL)

RUN TYPE	RADIUS	RADIUS DOWNLIGHTS	TOTAL DOWNLIGHTS
☒ - CAPSULE ☐ - CAPSULE	30"	2	20
5' (5' LONG)			
14' (14' LONG)			



Step 1: Select width: **2'-10'**

Step 2: Select length: **4'-100'**

Step 3: Select the number of downlights in radius segments

Step 4: Select the number of downlights

Configurator Logic: Downlight options scale with diameter selection

RADIUS / RADIUS DOWNLIGHTS
30" RADIUS / 2 DOWNLIGHTS

USE ONLINE CONFIGURATOR TO SPECIFY THIS PRODUCT LINE. [CONFIGURE](#)

L-SHAPE / U-SHAPE / SQUARE / RECTANGLE

RUN TYPE		RADIUS	RADIUS DOWNLIGHTS	TOTAL DOWNLIGHTS
U - U-SHAPE		18"	2	14
12' (12' LONG)	-----			
8' (8' LONG)	-----			
10' (10' LONG)	-----			


Step 1: Select lengths (2'-100' each side)

Step 2: Select soft corner radius (12"-60")

Step 3: Select number of downlights in radius segments

Step 4: Select the total number of downlights

Configurator Logic: The lengths of each side dictate the soft corner radius size available. Once radius is selected, choose the number of downlights within the radius from the drop down list. Choose the total number of downlights within the entire run from the drop down list. Downlights are distributed proportionally along straight sides according to length, with on-center spacing rules applied automatically.



CUSTOM

RUN TYPE	RADIUS	RADIUS DOWNLIGHTS	TOTAL DOWNLIGHTS
CUS - CUSTOM ✕	----- ▼	----- ▼	----- ▼

Option 1: CAD Layout

Download CAD blocks from the product page and create your layout using available modules in your preferred **CAD software**, submit a PDF or **DWG/DXF file**.


Modules:

- **Radius options:** 12", 18", 24", 30", 36", 42", 48", 54", 60"
- **Angle segments:** 30°, 45°, 60°, 90°
- **Straight runs:** available in **6" increments**

Configurator Logic: 3G reviews all custom submissions and returns a validated layout with part numbers, downlight counts, sectioning, and circuit guidance.

Option 2: Sketch

Submit a simple sketch with dimensions, number of downlights and spacing, and we'll generate the closest configuration.



Declare® is a product transparency program administered by the International Living Future Institute (ILFI), providing standardized disclosure of product ingredients, manufacturing location, service life, end-of-life pathways, and Living Building Challenge compliance status.

PRODUCT FAMILY COVERAGE — CHANNEL SYSTEMS

Architectural channel systems for recessed, surface, and suspended applications, including straight and curved configurations. Designed to integrate luminaires with mechanical systems, including HVAC and sprinkler systems, within coordinated ceiling layouts.

LBC RED LIST FREE

This product family carries a Declare® designation of LBC Red List Free, the highest designation within the Declare program. Products with this designation contain no intentionally added Red List chemicals above applicable Declare reporting thresholds and have been evaluated against the Living Building Challenge Red List.



BUILDING CERTIFICATION PROGRAMS

Material transparency documentation is increasingly requested as part of building certification programs and owner standards. Declare labels may be used as supporting documentation for project teams pursuing:

- Living Building Challenge (LBC)
- WELL Building Standard™ v1
- WELL Building Standard™ v2
- LEED®
- Other material disclosure and material health initiatives

Project certification requirements are determined at the building level and should be evaluated by the project team.

Declare.

Channel Systems 3G Lighting

Final Assembly: Woodbridge, Ontario, Canada

Life Expectancy: 7+ Year(s)

End of Life Options: Recyclable (95%), Landfill (5%)

Ingredients:

Aluminum UNS A96063; Steel, cold roll UNS G10080; Aluminum; Pulp, cellulose; Nylon 6; 2-Propenoic acid, butyl ester, polymer with ethenylbenzene and 2-propenenitrile; Carbonic dichloride, polymer with 4,4'-(1-methylethylidene)bis[phenol]; Paper; Soda lime; Starch, base-hydrolyzed, borated; Magnesium; 2,4,8,10-Tetraoxa-3,9-diphosphaspiro[5.5]undecane, 3,9-bis[2,4-bis(1,1-dimethylethyl)phenoxy]-; Vinyl acetate; Silicon; 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| ☒ LBC Red List Free | % Disclosed: 100% at 100ppm |
| ☐ LBC Red List Approved | VOC Content: Not Applicable |
| ☐ Declared | |

I-10 Interior Performance: Not Applicable

I-14 Responsible Sourcing: Not Applicable

GLG-0003

EXP. 01 JUN 2027

Original Issue Date: 2026

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY
INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare