
2 LIGHT DOWNLIGHT, 3 LIGHT DOWNLIGHT
3” FIXED DUAL, 3” FIXED TRIPLE APERTURE


SQUARE TRIMLESS




ⓘ THE IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSES ONLY AND MAY NOT BE AN EXACT REPRESENTATION OF THE PRODUCT

INCLUDED COMPONENTS


NCF - NEW CONSTRUCTION FRAME (FOR NEW CONSTRUCTION ONLY)




NEW CONSTRUCTION HOUSING




BAR HANGERS (OPTIONAL)



MUDDING FLANGE



BEVELED INSERT




SUCTION CUP

INSTRUCTION KEY	INFORMATION
⚠ ADDITIONAL	INSTALLATION SHOULD ONLY BE PERFORMED BY A CERTIFIED ELECTRICIAN
ⓘ ATTENTION	REFER TO LOCAL/NATIONAL CODES FOR PROPER INSTALLATION
POWER ON	FAILURE TO FOLLOW INSTALLATION INSTRUCTION MAY VOID THE WARRANTY
POWER OFF	DO NOT TOUCH LEDS. LEDS MUST BE PROTECTED FROM MECHANICAL STRESS OR DEBRIS
	TURN OFF POWER DURING INSTALLATION OR SERVICING


2 LIGHT DOWNLIGHT, 3 LIGHT DOWNLIGHT
3" FIXED DUAL, 3" FIXED TRIPLE APERTURE
SQUARE TRIMLESS

INSTALLATION INSTRUCTIONS


1 BAR HANGER INSTALLATION
(IF SUPPLIED BY 3G)



2




3 OTHER BAR HANGER INSTALLATION
(NOT PROVIDED BY 3G)




BUTTERFLY BRACKET
SIDE VIEW

4



5




WIRING LEGEND

BLACK	HOT/LINE
WHITE	NEUTRAL
GREEN	GROUND
ORANGE	(DIM-)
PURPLE	(DIM+)

MAKE WIRING CONNECTIONS


6 CEILING CUTOUT




FIXTURE TYPE	CEILING HOLE SIZE
DL33RF	3.625" x 3.625"

INSTALL CEILING BELOW FIXTURE


7



7A




8




APPLY MUDDING COMPOUND (BYO THERS) TO CEILING

9




9A



CONNECT SAFETY CABLE & QUICK-CONNECT CABLE TO LED ASSEMBLY


RMD - REMODEL WITH REMOTE DRIVER ENCLOSURE

1 REMOTE DRIVER WIRING



FOR REMOTE EMR DRIVER BOX, MAKE WIRED CONNECTIONS INSIDE PROVIDED LED CONNECTION ENCLOSURE


2



MAKE WIRING CONNECTIONS


LED SERVICING

1




REMOVE LED INSERT FROM CEILING WITH PROVIDED SUCTION CUP

1A




DISCONNECT SAFETY CABLE & QUICK-CONNECT CABLE FROM LED ASSEMBLY

2




3




DRIVER SERVICING

1




REMOVE LED INSERT FROM CEILING WITH PROVIDED SUCTION CUP

1A




DISCONNECT SAFETY CABLE & QUICK-CONNECT CABLE FROM LED ASSEMBLY

2




LOOSEN THUMB SCREW AND REMOVE DRIVER PLATE FROM CEILING

3



4



DISCONNECT 5-WIRE CONNECTOR