



3G-PMZ4

4 LIGHT LINEAR ZOIE PENDANT

4 Light high performance pendant with 1" apertures
Narrow 1.5" aperture with one piece extruded aluminum housing
LED system delivers over 800lm at 90+ CRI
Features matte black or matte white multi-faceted louvers
Regressed LED source with enhanced glare control, UGR <16
100-1% dimming range standard with remote drivers



ORDERING INFORMATION

PROJECT:	<input type="text"/>	TYPE:	<input type="text"/>
CATALOG #:	<input type="text"/>	DATE:	<input type="text"/>

CAT. NO	LUMEN OUTPUT	CRI	COLOR TEMP	BEAM ANGLE	VOLTAGE
3G-PMZ4	04 - 400 LUMENS	H90 - 90+ CRI	27K - 2700K	15D - 15°	UNV - 120/277V 120 - 120V
	08 - 800 LUMENS		30K - 3000K	35D - 35°	
			35K - 3500K	55D - 55°	
			40K - 4000K		

DRIVER	HOUSING FINISH	ZOIE LOUVER FINISH	CABLE LENGTH
RDIM - REMOTE 0-10V (100-1%) RDALI - REMOTE DALI (100-1%) RD01 - REMOTE 0-10V (100-0.1%) RDHL2 - REMOTE LUTRON HI-LUME LDE (1% ECOSYSTEM)	BK - BLACK WH - WHITE SV - SILVER All mounting canopies provided in white as standard	BLV - BLACK WLV - WHITE	60 - 60" (STANDARD) 120 - 120"

JUNE 7, 2023


PERFORMANCE CHART BASED ON 35° 90+CRI LED SOURCE

LUMEN OUTPUT	COLOR TEMP	DELIVERED LUMENS	SYSTEM WATTS	EFFICACY (LPW)
08 - 800 LUMENS	27K	684	9.6	71
	30K	745	9.6	78
	35K	822	9.6	86
	40K	838	9.6	88


REMOTE POWER SUPPLY OPTIONS

3G DRIVER CODE	DIMMING METHOD	DIMMING RANGE	VOLTAGE	MAX. DISTANCE	3G-PMZ4 (9.6W)	3G-PMZ8 (19.2W)	3G-PMZ12 (28.5W)
RDIM	0-10V	100-1%	120-277V	100ft (12 AWG)	1 to 4	1 to 2	1
RDHL2	LUTRON HI-LUME LDE ECOSYSTEM	100-1%	120-277V	100ft (12 AWG)	2 to 4	1 to 2	1
RDALI	DALI ELDOLED	100-1%	120-277V	100ft (12 AWG)	1 to 4	1 to 2	1
RD01	0-10V ELDOLED	100-0.1%	120-277V	100ft (12 AWG)	1 to 4	1 to 2	1

REMOTE POWER SUPPLY ENCLOSURE



WIRING DIAGRAM



Multiple Zoie fixtures must be connected in series

TECHNICAL**HOUSING**

Extruded aluminum housing with narrow 1.5" aperture

Machined aluminum end caps

Standard polyester powder coated housing finish available in matte white, black, and silver

Matte black and matte white faceted louver finishes

OPTICS

1" apertures with regressed LED source for enhanced glare control

Proprietary polycarbonate multi-faceted reflectors

Available in 15°, 35° and 55°

UGR <16

ELECTRICAL

Remote 0-10V, constant current driver with 100-1% dimming range

Remote 0-10V, constant current driver with 100-0.1% dimming range

Remote Lutron EcoSystem and eidoLED DALI options (100-1% dimming)

LED SYSTEM

Osram LED source

Color consistency <2 SDCM

Standard 90+ CRI

Available in 27K, 30K, 35K, and 40K

L90 >60,000 hours

5 year warranty

MOUNTING

Adjustable aircraft cable suspension with locking fasteners (60" length standard)

Standard, 18-gauge, 5 conductor single circuit power feed (clear braided finish)

All mounting canopies provided in white finish as standard

Suitable for various architectural ceilings (see mounting details)

LISTING

ETL listed and conforms to UL1598 standard. Certified to CSA22.2 No.250.0. Rated for indoor locations


WARRANTY

5 year warranty on LED and drivers


Manufacturer 1 year warranty for defects in material and workmanship under normal use

Ambient temperature at fixture should not exceed 25°C

DRAWINGS AND DIMENSIONS



BEAM ANGLE



MOUNTING DETAILS

